HEAT-RESISTANT PAPER AND ITS PRODUCTION

Patent number:

JP9021089

Also published as:

Publication date:

1997-01-21

JP9021089 (A)

Inventor:

NISHIOMOTE KENJI; SONEDAKA TOMOYASU

Applicant:

KURARAY CO LTD

Classification:

- International:

D21H13/24

- european:

Application number:

JP19950170895 19950706

Priority number(s):

Abstract of JP9021089

PROBLEM TO BE SOLVED: To obtain heat-resistant paper by making paper from a pulp component comprising a melt liquid crystal polyester and a fiber component having low dry heat shrinkage in a wet state, hot pressing the paper, having both heat resistance and mechanical strength, suitable for electric insulating paper, a building material, etc.

SOLUTION: A pulp composition comprising a melt liquid crystal polyester obtained by polymerizing p-hydroxybenzoic acid with 2-hydroxy-6-naphthoic acid is mixed with 5-50wt.%, preferably 20-40wt.% of a glass fiber, etc., having \$5%, preferably <=2% dry hot shrinkage factor as a fiber component and made into paper in a wet state. Then the paper is hot pressed at 180-300 deg.C, preferably 240-290 deg.C under 50-250kg/cm, preferably 100-250kg/cm linear pressure to give the objective heat resistant paper having <=3% dry heat shrinkage factor and >=50kg/6mm release strength.

Data supplied from the esp@cenet database - Worldwide